








- Clean Face Look No Louvers
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 17½" x 19¾", 345½ in²
- Classic Log Set
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty
- Quick Access Valve Controls

Available Options

- Remote or Thermostat Control
- Glass, Coal, or Log Set
- Liners Options:
- Brick Liner with Logs
- Black Enameled Liner with Glass or Logs
- Ledgestone Liner
- Surround Options:
 - Cast Face
 - Modern Surround
 - Contemporary Surround w/Trimmable Panel
 - Trimmable Panel

Insert Specifications

· · · · · · · · · · · · · · · · · · ·				
BTU Maximum Input - NG	2	0,000 BT	U	
BTU Minimum Output*	7	7,900 BTU	J	
Heating Area		1,000 ft ²		
P4 Efficiency	74.5%			
Glass Size		345½ in²		
Minimum Install Dims.	HEIGHT 271/2"	WIDTH 201/4"	DEPTH 141⁄4″	





Classic Log Set



Coal



Glass Burner with Diamond Glass



- Clean Face Look No Louvers
- Cast Iron Heat Exchanger
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 21¾" x 13¾", 300 in²
- Classic Log Set
- Easy Access Burner Switch
- 110 CFM Room Fan (with variable control)
- Limited Lifetime Warranty

Available Options

- Hearth Riser
- Remote or Thermostat Control
- Glass or Classic Log Set
- Liner Options:
- Brick or Fluted Liner with Logs
- Black Enameled Liner with Glass or Logs
- Surround Options:
- Modern Surround– Contemporary Surround
- Slim Surround
- Extruded Surround
- 4-Sided Extruded Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

ı				
BTU Maximum Input - NG	2	3,000 BT	U	
BTU Minimum Output*	8,000 BTU			
Heating Area		1,200 ft ²		
P4 Efficiency	66.45%			
Glass Size		300 in ²		
Minimum Install Dims.	HEIGHT 181/4"	WIDTH 24 1/4"	DEPTH 14"	

 $^{^{}st}$ Turn down is based on a 50% valve and AFUE efficiencies output.



Fluted Liner with Log Set



Black Glass with Decorative Stones



Brick Liner with Log Set







- Clean Face Look No Louvers
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 26¼" x 16", 420 in²
- Three Different Log Sets
- Easy Access Burner Switch
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty

Available Options

- Hearth Riser
- Remote or Thermostat Control
- Classic & Driftwood Log Sets, Glass
- Liners Options:
- Brick Liner (Log Burner)
- Black Enameled Liner (Glass or Log Burner)
- Fluted Liner (Log Burner)
- Ledgestone Liner (Log Burner)
- Surround Options:
- Modern Surround
- Contemporary Surround
- Slim Surround
- Extruded Surround - 4-Sided Extruded Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

,				
BTU Maximum Input - NG	3	3,000 BT	U	
BTU Minimum Output*	1	0,000 BT	U	
Heating Area		1,700 ft ²		
P4 Efficiency	71.4%			
Glass Size		420 in ²		
Minimum Install Dims.†	HEIGHT 19 1/8"	WIDTH 27%"	DEPTH 16 "	

^{*} Turn down is based on a 50% valve and AFUE efficiencies output.



Brick Liner with Log Set



Glass Burner with Diamond Glass



Black Enameled Liner with Driftwood

 $^{\ \, \}text{\it + Based on installation with the Contempory Surround. Depth can vary by panel.} \\$







- Top Firebox Lighting
- Adjustable Ember Bed Lighting
- Clean Face Look No Louvers
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 261/4" x 16", 420 in²
- Ultra High Definition Log Set
- 150 CFM Room Fan (with variable control)
- Run-Quiet Fan System
- Limited Lifetime Warranty



Available Options

- Hearth Riser
- Remote or Thermostat Control
- Ultra High Definition Log Set
- Liners Options:
 Brick | Black Enameled | Fluted | Ledgestone
- Surround Options:
- Contemporary Surround
- Slim Surround
- Extruded Surround
- 4-Sided Extruded Surround
- Designer Series Surround
- Cast Plus Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

ı			
BTU Maximum Input - NG	3	2,500 BT	U
BTU Minimum Output*	1	6,000 BT	U
Heating Area		1,700 ft ²	
P4 Efficiency		75.4%	
Glass Size		420 in ²	
Minimum Install Dims.	HEIGHT 19 1/8"	WIDTH 27 1/8"	DEPTH 16"

^{*} Turn down is based on a 33% valve and P4 efficiencies output.



Ultra HD Log Set with Brick Liner



Designer Series Surround



Adjustable Ember Bed Lighting







- Clean Face Look No Louvers
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 28½" x 18", 513 in²
- Three Different Log Sets
- Easy Access Burner Switch
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty
- Quick Access Valve Controls Contemporary and Extruded Panels Only

Available Options

- Hearth Riser
- Remote or Thermostat Control
- Classic & Driftwood Log Sets, Glass, or Ceramic Rock Set
- Liners Options:
- Brick Liner (Log Burner)
- Black Enameled Liner (Glass or Log Burner)
- Fluted Liner (Log Burner)
- Ledgestone Liner (Log Burner)
- Surround Options:
- Modern Surround
- Contemporary Surround
- Slim Surround– Extruded Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

BTU Maximum Input - NG	U			
BTU Minimum Output*	1	1,000 BT	U	
Heating Area		1,800 ft ²		
P4 Efficiency	71.1%			
Glass Size		513 in ²		
Minimum Install Dims.†	HEIGHT 20"	WIDTH 32"	DEPTH 17½"	

^{*} Turn down is based on a 50% valve and AFUE efficiencies output.



Midnight Bronze Forgeworks Surround



Ceramic Rock Set



Log Set with Ledgestone Liner

[†] Based on installation with the Contempory Surround. Depth can vary by panel.







- Firebox Top Lighting
- Adjustable Ember Bed Lighting
- Clean Face Look No Louvers
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 28½" x 18", 513 in²
- Ultra High Definition Log Set
- 150 CFM Room Fan (with variable control)
- Run-Quiet Fan System
- Limited Lifetime Warranty



Available Options

- Hearth Riser
- Remote or Thermostat Control
- Ultra High Definition Log Set
- Liners Options:
 Brick | Black Enameled | Fluted | Ledgestone
- Surround Options:
- Contemporary Surround
- Slim Surround
- Extruded Surround
- Designer Series Surround
- Cast Plus Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

3	5,000 BT	U	
1	7,000 BTI	J	
	1,800 ft ²		
74.5%			
	513 in ²		
HEIGHT 20"	WIDTH 32"	DEPTH 17½"	
	1 HEIGHT	74.5% 513 in ² HEIGHT WIDTH	

^{*} Turn down is based on a 33% valve and P4 efficiencies output.



Firebox Top Lighting (Left=On, Right=Off)



Ultra HD Log Set with Fluted Liner



Cast Plus Surround







- Clean Face Look No Louvers
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 30 5/8" x 22 1/4", 681 in2
- Two Different Log Sets
- Remote Control Included
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty

Available Options

- Hearth Riser
- Thermostat Control
- Classic Log Set
- Liners Options:Brick | Black Enameled | Fluted | Ledgestone
- Surround Options:
- Modern Surround
- Cape Cod Doors
- Contemporary Surround
- Extruded Surround
- Borderview Surround | **ELITE EDITION**
- 4-Sided Extruded Surround
- Trimmable Panel

Insert Specifications

'			
BTU Maximum Input - NG	4	2,000 BT	U
BTU Minimum Output*	1	3,000 BT	U
Heating Area		2,300 ft ²	
P4 Efficiency		63%	
Glass Size		681 in ²	
Minimum Install Dims.†	HEIGHT 24"	WIDTH 34½"	DEPTH 203/8"

^{*} Turn down is based on a 33% valve and AFUE efficiencies output.



Cape Cod Doors



Hearth Riser



Log Set with Ledgestone Liner

[†] Based on installation with the Contempory Surround. Depth can vary by panel.

Surround Panels

ELITE EDITION | SURROUND PANELS



CONTEMPORARY
Available for the E20, E30, E33, EX32, EX35, & E44



MODERN
Available for the E20, E30, E33, & E44



BORDERVIEW

Available for the E20, E30, E33, EX32, EX35 & E44 (E44 only in Brushed Nickel)

Brushed Nickel • Brushed Antique Copper • Powder Coated Grey



BORDERVIEW PLUS

Available for the E20, E30, E33, EX32 & EX35

Brushed Nickel • Brushed Antique Copper • Powder Coated Grey



SLIMAvailable for the E20, E30, E33, EX32 & EX35



EXTRUDEDAvailable for the E20, E30, E33, EX32, EX35, & E44



DESIGNER SERIES SURROUND

Available for the EX32 & EX35

Brushed Nickel • Brushed Antique Copper • Powder Coated Grey

Powder Coated Silver • Powder Coated Bronze



MODERN PLUS

Available for the E20, E30, E33, EX32 & EX35

Powder Coated Grey



CAPE COD DOORS

Available for the E44



4 - SIDED EXTRUDED Available for the E20, E30, & E44



EXTRUDED PLUSAvailable for the E20, E30, E33, EX32 & EX35
Powder Coated Grey



FORGEWORKS

Available for the E30, E33, EX32 & EX35

Midnight Bronze



Q1 MODERN Available for the Q1



CONTEMPORARY W/TRIMMABLE PANEL
Available for the Q1



BORDERVIEW PLUS 4S

Available for the E20 & E30

Powder Coated Grey




CAST PLUS SURROUND
Available for the EX32 & EX35

Unit Specifications

Performance	Q1 PORTRAIT GAS INSERT	E20 SMALL GAS INSERT	E30 / EX32 MEDIUM GAS INSERTS	E33 / EX35 LARGE GAS INSERTS	E44 EXTRA LARGE GAS INSERT
BTU Maximum input - NG/LP	20,000 / 18,500	23,000 / 21,300	E30 - 33,000 / 28,000 EX32 - 32,500 / 31,000	E33 - 34,000 / 31,000 EX35 - 35,000 / 35,000	42,000 / 36,000
Turn Down - Valve 820 / Valve 885	50% / 33%	50% / 33%	50% / 33%	50% / 33%	N/A / 33%
Heat Exchanger	Steel	Cast Iron	Steel	Steel	Steel
SIT Valve 820 (Standing Pilot)	Available	Available	E30: Available / EX32: N/A	E33: Available / EX35: N/A	N/A
SIT Valve 885 (IPI)	Available	Available	E30: Available / EX32: Standard	E33: Available / EX35: Standard	Available
Efficiency - Steady State*	76.19%	72.39%	E30: 78.72% / EX32: 73.48%	E33: 77.64% / EX35: 76.1%	66.91%
Efficiency - FE rating**	74.45%	66.45%	E30: 71.4% / EX32: 74.97%	E33: 71.13% / EX35: 74.11%	58.49%
Glass Size	17½" x 19¾", 345½ in²	21¾" x 13¾", 300 in²	26¼" x 16", 420 in²	28½" x 18", 513 in²	30 ¾" x 22¼", 681 in²
Convection Fan	150 CFM	110 CFM	150 CFM	150 CFM	150 CFM

Installation	Q1 PORTRAIT GAS INSERT	E20 SMALL GAS INSERT	E30 / EX32 MEDIUM GAS INSERTS	E33 / EX35 LARGE GAS INSERTS	E44 EXTRA LARGE GAS INSERT	
Min. Install Dims. †	HEIGHT WIDTH DEPTH 27 1/2" 20 1/4" 14 1/4"	HEIGHT WIDTH DEPTH 181/4" 241/4" 14"	HEIGHT WIDTH DEPTH 197/8" 277/8" 16"	HEIGHT WIDTH DEPTH 20" 32" 17½"	HEIGHT WIDTH DEPTH 24" 34½" 20¾8"	
LP Conversion Kit (SP)	Standard	Standard	E30: Standard / EX32: N/A	E33: Standard / EX35: N/A		
LP Conversion Kit (IPI)	Optional	Optional	Optional	Optional	Optional	
Venting (Direct Vent)	3" x 3"	3" x 2"	3" x 3"	3" x 3"	3" x 3"	
Weight	110 lbs	90 lbs	116 lbs	135 lbs	210 lbs	
Wood ZC Fireplace Approved	Standard	Standard	Standard	Standard	Standard	
ZC Floor Removal Approved	Standard		E30: 2¼" Raise / EX32: ½" Raise	E33: 4" Raise / EX35: 3½" Raise	:	

Clearance to Combustibles	Q1	E20	E30 / EX32	E33 / EX35	E44
A - center of unit to side wall	16½"	19½"	21"	24"	23½"
B - bottom of unit to bottom of 12" mantle	41"	39¾"	36" (EX32 42")	36"	40"
C - unit bottom to max. 3/4" combustible facing	351/4"	37½"	30" (EX32 33")	30"	40"
D - center of unit to side facing	10"	16½"	21"	23"	23"
E - front of door to edge of floor protection	12"	13"	16" (EX32 9")	16" (EX35 9")	16"‡



Available Options

Surround Panels	PORTRAIT			20 AS INSERT		EX32 AS INSERTS		EX35	EXTRA LARG	I .4 GAS INSERT
Contemporary Surround	HEIGHT	WIDTH	HEIGHT 23 7/8"	WIDTH 35 3/8"	HEIGHT	WIDTH 39 3/4"	HEIGHT 26 ½"	WIDTH 44 1/8"	HEIGHT 30 1/8"	WIDTH 45"
Oversize Contemporary Surround			26 7/8"	373/8"	29"	397/8"	29"	441/8"		
Extruded Surround			23 7/8"	353/8"	25 1/8"	39¾"	261/2"	441/8"	30 1/8"	45"
Oversize Extruded Surround					29"	39¾"	29"	44 1/8"		
Modern Surround Not available for the EX32 or EX35	30"	30"	23 7/8"	35 3/8"	25"	397/8"	261/2"	43 ½"	30 1/8"	45"
Slim Surround			21"	293/4"	22"	33 1/4"	221/4"	36"		
Cape Cod Doors									30"	42"
4-Sided Extruded Surround			29 5/8"	35 3/8"	31½"	39¾"			37"	45"
Contemporary Sur. w/Trimmable Panel	32"	36"								
Borderview Surround – EE			24"	37 1/4"	26 1/8"	40"	25 1/8"	42"	28 3/4"	45"
Borderview Plus Surround – EE			24"	37 1/4"	26 ½"	40"	25 1/8"	42"		
Extruded Plus Surround – EE			24 1/8"	36 ⁷ / ₈ "	26"	40"	25 1/8"	42"		
Modern Plus Surround – EE			225/8"	341/4"	25 3/8"	381/2"	245/8"	39"		
Borderview Plus 4S Surround – EE			267/8"	35 ¾"	31"	40"				
Forgeworks Surround – EE					26 1/8"	40"	25 1/8"	42"		
Designer Series Surround – EE EX32/EX35 Only					241/2"	385/8"	25"	41 3/4"		
Oversize Designer Series Surround – EE EX32/EX35 Only					30	43 3/4"	30"	45 3/4"		
Cast Plus Surround – EE EX32/EX35 Only					243/4"	393/8"	25 1/4"	42 1/4"		
Oversize Cast Plus Surround - EE EX32/EX35 Only					30	393/8"	32"	43 3/4"		
Trimmable Panel	32"	36"	28 3/4"	41 ¾"	38"	46"	38"	46"	36"	55"
4-Sided Trimmable Panel			393/8"	41 ¾"	41 1/8"	46"			47"	55"
Firebox Liners	Q PORTRAIT (!1 GAS INSERT		20 AS INSERT		EX32 AS INSERTS		EX35 S INSERTS	E4	_
Brick Liner	•	•	•	/	•	/	•	/	· ·	•
Black Enameled Steel Liner	٧		•	/	•	/	•	/		•
Fluted Liner			•		•	/	•			•
Ledgestone Liner	•				•	•	•		•	•
Burner Variations	Q PORTRAIT (1 GAS INSERT		20 AS INSERT		EX32 AS INSERTS		EX35	EZ EXTRA LARG	!4 : GAS INSER
Log Set (Ultra HD for EX32/EX35)	Cla	ssic	Cla	ssic	Classic /	Ultra HD	Classic /	Ultra HD	Cla	ssic
Driftwood Log Set					E30	Only	E33	Only		
Glass Burner (Black Glass)	Diamor	nd Glass	Diamor	nd Glass	Diamoi	nd Glass	Diamor	nd Glass		
Ceramic Rock Set							E33	Only		
	_		_							

Ceramic Rock Set				E33 Only	
Additional Options	Q1 PORTRAIT GAS INSERT	E20 SMALL GAS INSERT	E30 / EX32 MEDIUM GAS INSERTS	E33 / EX35 LARGE GAS INSERTS	E44 EXTRA LARGE GAS INSERT
Decorative Stones (Glass Tray Burners Only)		~	~		
Firebox Lights (Top & Bottom)			EX32 Standard	EX35 Standard	
Hearth Riser (N/A with 4-Sided Surround Panels)		2"H 40¾"W	2"H 43½"W	2"H 45½"W	1½"H 46¾"W
Programmable Thermostat	✓	~	✓	~	✓
Proflame Remote Control	Standard with IPI	Ontional	Standard with IPI	Standard with IPI	Standard

Optional with 820 Nova Optional with 820 Nova

Optional with 820 Nova

Proflame Remote Control

^{*} Steady State based on measured rating of IPI model.

^{**} FE Rating based on measured P.4 rating of IPI model.

[†] Based on installation with the Contemporary Surround. Depth can vary by panel. A more detailed breakdown can be found in the owner's manual.

[‡] Based on a minimum ½" raised hearth (18" flush).

EE Elite Edition Surround Panel

The best way to visualize your dream fireplace at home is with the Enviro App!





















